

Show the world your **true colors**.



**Spyder4<sup>ELITE</sup>**

**Spyder4<sup>PRO</sup>**

**Spyder4<sup>EXPRESS</sup>**

**SOFTWARE SPECIFICATIONS**

Gamma Choices	Unlimited	1.8, 2.0, 2.2, 2.4	2.2
Color Temperature Choices	Unlimited	5000K, 5800K, 6500K, native	6500K
Special Targets	NTSC, PAL/SECAM, Cineon, L-Star*	64 patches	64 patches
ICC Profile Support	ICC 2, ICC 4	ICC 2, ICC 4	ICC 2
Multiple Display Calibration	✓	✓	—
TV Calibration	✓ upgrade available on website at additional cost	✓ upgrade available on website at additional cost	—
Front Projector Calibration	✓	—	—
Ambient Light Measurement	✓	✓	—
Re-calibration Wizard	✓	✓	—
Expert Console	✓	—	—
Custom B/W Luminance Control	✓	—	—
Display History Utility	✓	—	—
SpyderProof Interface	✓	✓	✓
StudioMatch	✓	—	—
Gamma Curve Editing	✓	—	—
Real-time Profile & Calibration Check	✓	✓	✓
L-Star Workflow Option	✓	—	—
Curves Import Function	✓	—	—
SpyderTune	✓	—	—
Iterative Gray Balance	✓	—	—

**HARDWARE SPECIFICATIONS**

Measurement Device	Spyder4 <sup>ELITE</sup>	Spyder4 <sup>PRO</sup>	Spyder4 <sup>EXPRESS</sup>
Ambient Light Sensor	✓	✓	—
Color Sensor	7 Filter/Detector	7 Filter/Detector	7 Filter/Detector
Aperture Size	27 mm	27 mm	27 mm
Initial Calibration Time	5 Minutes	5 Minutes	5 Minutes
Recalibration Time	2.5 Minutes	2.5 Minutes	—
Ambient Light Shield	2 Inches	2 Inches	2 Inches
Mounting Methods	Universal Counterweight and Tripod Mount	Universal Counterweight and Tripod Mount	Universal Counterweight
Desktop Docking Base w/Tripod Mount	✓	✓	—
Physical Dimensions	1.5 in.(D) x 3.5 in.(W) x 4 in.(L)	1.5 in.(D) x 3.5 in.(W) x 4 in.(L)	1.5 in.(D) x 3.5 in.(W) x 4 in.(L)
Computer Connection	USB	USB	USB
Web Registration & Update Checks	1 Year (for countries of the EU, the period is 2 years)	1 Year (for countries of the EU, the period is 2 years)	1 Year (for countries of the EU, the period is 2 years)

\* L-Star technology is Licensed Property of INTEGRATED COLOR SOLUTIONS, INC., Patent No. 7,075,552 and No. 6,937,249.